



Shown with optional fuel filler installed, lighted bumper and cantilever rack

R-SERIES: PREMIUM ROLL-UP DOORS

STANDARD FEATURES

- All Aluminum (6000 Series) Understructure with Extruded Box Tube Construction
- Heavy Slam Latch Tailgate with Stainless Steel Lock Rods
- Premium Roll-Up Safety Designed Doors
- Extreme Duty (6000 Series). 625 Interlocking Extruded Aluminum Floor
- Fully Welded Construction—No Rivets, Screws, Bolts to Come Loose
- Welded Fender Flares for Superior Strength and Rigidity

- Sandblasted Metal Preparation (not inferior wash/zinc phosphate)
- Powder Coated—Standard: White Optional colors available:
 - Black
 - Red: GM/Dodge Red & Ford Red
- LED Marker Lights (where required)
- LED Penny Light in Each Compartment
- LED Ultra-thin 6" Round Stop/Turn/Tail/ Backup Body Lights

• Inner Bed Walls and Exterior Top of Compartments—1/8" Diamond Plate

DISTRIBUTED BY:

- Adjustable Shelving in Front, Middle, and Rear Compartments (one shelf with dividers in each compartment)
- Pass through Panel between Front & Center Compartments
- Tread Plate Splash Guards on Front Wall—ALL Models
- Strongest Built Aluminum Service Body in the Industry
- BEST 10 YEAR WARRANTY in the Industry



Strongest Understructure in the Industry



Center Compartment with Dropdown Door (showing Double Walled Doors)



Pass Thru Compartment Shown Between Front and Middle Boxes



Tread Plate Rock Guards on Front Wall



LED Ultra-thin 6" Round Stop/Tail/Turn/Backup Body Lights



7' SERVICE BODIES

| Model | DuraMag Aluminum Weight (lbs) | Typical Steel Weight (lbs) | % Lighter Than Steel | Cab to Axle | Compartment Door Openings | | |
|------------------|----------------------------------|-------------------------------|-------------------------|-------------|---------------------------|--------------------|---------------------|
| | | | | | Front | Middle | Rear |
| SB-R-36D-STD-SRW | 582 | 874 | 33% | 36" | 49-1/16" x 15" | 21-3/16" x 32-3/4" | 20-5/16" x 33-3/16" |
| SB-R-40F-STD-SRW | 665 | 964 | 31% | 40" | 57-11/16" x 15" | 21-3/16" x 32-3/4" | 20-5/16" x 33-3/16" |
| SB-R-42G-STD-SRW | 670 | 1,009 | 34% | 42" | 57-11/16" x 15" | 21-3/16" x 32-3/4" | 20-5/16" x 33-3/16" |

8.5' SERVICE BODIES

| Model | DuraMag Aluminum Weight (lbs) | Typical Steel Weight (lbs)) | % Lighter Than Steel | Cab to Axle | Compartment Door Frame Opening Clearance | | |
|-----------------|----------------------------------|--------------------------------|-------------------------|-------------|--|----------------|--------------------|
| | | | | | Front | MIddle | Rear |
| SB-R-56-STD-SRW | 811 | 1,111 | 37% | 56" | 23-15/16" x 32-3/4" | 43-3/16" x 15" | 21-3/16" x 32-3/4" |
| SB-R-56-STD-DRW | 895 | 1,288 | 43% | 56" | 23-15/16" x 32-3/4" | 43-3/16" x 15" | 21-3/16" x 32-3/4" |

9' SERVICE BODIES

| Model | DuraMag Aluminum Weight (lbs) | Typical Steel Weight (lbs) | % Lighter Than Steel | Cab to Axle | Compartment Door Frame Opening Clearance | | |
|-----------------|----------------------------------|-------------------------------|-------------------------|-------------|--|----------------|--------------------|
| | | | | | Front | Middle | Rear |
| SB-R-60-STD-SRW | 820 | 1,238 | 51% | 60" | 28-3/16" x 32-3/4" | 43-3/16" x 15" | 26-3/16" x 32-3/4" |
| SB-R-60-STD-DRW | 912 | 1,399 | 53% | 60" | 28-3/16" x 32-3/4" | 43-3/16" x 15" | 26-3/16" x 32-3/4" |

11' SERVICE BODIES

| Model | DuraMag Aluminum Weight (lbs) | Typical Steel Weight (lbs) | % Lighter Than Steel | Cab to Axle | | | |
|-----------------|----------------------------------|-------------------------------|-------------------------|-------------|--------------------|----------------|--------------------|
| | | | | | Front | Middle | Rear |
| SB-R-84-STD-DRW | 1,124 | 1,704 | 52% | 84" | 52-3/16" x 32-3/4" | 43-3/16" x 15" | 26-7/16" x 32-3/4" |