

**ANTHONY**  
LIFTGATES, INC.®

**ATU-GLR**



## TUCKUNDER™ SERIES

LIFTING CAPACITIES (LBS): 2500, 3000

### KEY ADVANTAGES

- 1. GLR - Gentle Level Ride**  
Smooth, level up/down operation. Platform tilts gently at ground and re-levels before lifting cycle begins.
- 2. Spring Assist Wedge Platform**  
Dual torsion springs provide effortless platform operation.
- 3. Lifetime Warrantied Service Free Bushings**  
Used at all critical pivot points to reduce wear without the need for routine lubrication.
- 4. EZ Mount**  
Ships factory assembled, filled, and tested with notched center mark for easy installation. Floor extension may be bolted to the truck.
- 5. CHS - Centralized Hydraulic System**  
All sensitive hydraulic and electrical components housed safely within the stainless steel pump box.



**QUALITY, RELIABILITY, CUSTOMER SERVICE**

**MADE IN THE USA** 

## STANDARD FEATURES

- **HD Mechanical Safety Latch**  
Redundant-system stowage in addition to hydraulic lock.
- **Max Duty Dock Bumpers**  
Helps protect floor extension from contact with dock. Includes rubber bumpers.
- **Marine Duty Potted Toggle Switch**  
Heavy duty toggle, potted to permanently separate and seal electrical connections from corrosion.
- **Circuit Protection**  
200 Amp fuse protects truck wiring from a "dead short".
- **3/16" Steel Floor Extension**  
Rugged and attractive surface.
- **Industry-Leading Warranty**  
3 years mechanical + 3 years electrical & hydraulic, parts and labor.
- **Pressure Compensated Flow Valve**  
Constant, controlled speeds at all times. Prevents "free-fall" under certain hydraulic failures.
- **Anthony 3-Step Powder Coat**  
Steel components are washed, shot blast prepped, and coated with premium finish.

## QUALITY COMES STANDARD

### AVAILABLE MODELS, PLATFORMS AND CAPACITIES

Model	ATU-GLR-2500	ATU-GLR-3000
Capacity (lbs)	2500	3000
Bed Height Range	42" - 55"	
Available Platforms	Steel 80" x 50" Wedge (standard)* Aluminum 80" x 50" Wedge* Steel 80" x 48" + 12" Aluminum Retention Ramp	

\*Cart stops available. 39" load area when deployed.

### OPTIONS

- Cart stops
- Power down
- Alternate floor extensions: 3/16", 1/4", or 3/8" steel. 96" or 102" Wide.
- Wireless, removable handheld corded, flush mount, or dual control options.
- Stainless steel toggle switch guard
- Third step add-on for dock bumper
- Galvanized finish with extended warranty
- ICC Bumper
- Cab or ignition cutoff switch
- Battery Box

### TRUCK MOUNTING REQUIREMENTS

A	B	C	
Bed Height	Bed to top of Tube Assembly	Mounting Plate	<p>Bed Extension 12" (Reference)</p> <p>Body Crossmembers</p> <p>Body Long Sills</p> <p>Wood Filler</p> <p>Chassis Frame</p> <p>Liftgate Mounting Plate</p> <p>Pump Box Extends 3 1/2" Forward of Mounting Plate</p>
42" - 49"	19"	24 1/4"	
50" - 51"	20"	23 3/4"	
52" - 53"	21"	23 1/4"	
54" - 55"	22"	22 5/8"	
56" - 57"	23"	22 1/2"	

### Anthony Liftgates, Inc.

1037 W. Howard Street  
P.O. Box 615  
Pontiac, IL 61764-0615

**Phone:** 815.842.3383

**Fax:** 815.844.3612

**Toll Free:** 800.482.0003

**www.anthonyliftgates.com**